

# Vector™ VS330™ GNSS Compass

## Professional Heading and Positioning Receiver

### key features

- Extremely accurate heading with baselines greater than 50 m
- Dual frequency GPS/GLONASS RTK capable
- L-Band DGNSS/HP/XP (OmniSTAR®) and Beacon capable
- Automatic Antenna Baseline Survey
- Maintain heading and position lock when more of the sky is blocked
- RTK, L-Band DGNSS, Beacon and SBAS capable
- COAST™ technology maintains differentially-corrected positioning for 40 minutes or more after loss of differential signal
- Integrated gyro and tilt sensors help deliver fast start-up times and provide heading updates during temporary loss of satellites



Experience the Vector™ VS330™ with Eclipse™ GNSS technology, an addition to our Vector VS family. Developed for precise marine, dynamic positioning, and land applications requiring precise heading and RTK position performance.

The Vector VS330 utilizes all of the innovations in Hemisphäre GNSS' Eclipse™ Vector technology. Our optimized Eclipse Vector technology brings a series of new features to the Vector VS330 including heave, pitch, and roll output, and more robust heading and positioning performance.

The Vector VS330 receiver, with its display and user interface, can be conveniently installed near the operator. The two antennas are mounted separately and with a user-determined separation to meet the desired heading accuracy. The Vector VS330 uses L-Band DGNSS (VBS/HP/XP/G2) and SBAS for differential GNSS positioning. Our MFA DGNSS patented technology allows the VS330 to smoothly transition between DGNSS systems.



# Vector VS330 GNSS Compass

## GNSS Sensor Specifications

Receiver Type: Vector GNSS L1/L2 RTK Receiver  
Signals Received: GPS, GLONASS  
Channels: 540  
GPS Sensitivity: -142 dBm  
SBAS Tracking: 3-channel, parallel tracking  
Update Rate: 10 Hz standard, 20 Hz optional

## Positioning Accuracy:

RMS:	Horizontal	Vertical
Single Point <sup>1</sup> :	1.2 m	2.5 m
SBAS (WAAS) <sup>2</sup> :	0.3 m	0.6 m
L-Band DGNSS (HP) <sup>3</sup> :	0.1 m	0.2 m
Code Differential GNSS <sup>1</sup> :	0.3 m	0.6 m
RTK <sup>2,4</sup> :	10 mm + 1 ppm	20 mm + 2 ppm
Heading Accuracy:	0.17° rms @ 0.5 m antenna separation 0.09° rms @ 1.0 m antenna separation 0.04° rms @ 2.0 m antenna separation 0.02° rms @ 5.0 m antenna separation 0.01° rms @ 10.0 m antenna separation	

Pitch/Roll Accuracy (RMS): 1°  
Heave Accuracy (RMS): 30 cm (DGPS) <sup>5</sup>, 10 cm (RTK) <sup>2,4</sup>  
Timing (1PPS) Accuracy: 20 ns  
Rate of Turn: 100°/s maximum  
Compass Safe Distance: 30 cm (with enclosure) <sup>6</sup>  
Cold Start: 60 s (no almanac or RTC)  
Warm Start: 20 s typical (almanac and RTC)  
Hot Start: 1 s typical (almanac, RTC and position)  
Heading Fix: 10 s typical (valid position)  
Maximum Speed: 1,850 mph (999 kts)  
Maximum Altitude: 18,288 m (60,000 ft)  
Differential Options: SBAS, Beacon, External RTCM, L-Band (VBS/HP/XP/G2) and RTK

## Beacon Sensor Specifications

Channels: 2-channel, parallel tracking  
Frequency Range: 283.5 to 325 kHz  
Operating Modes: Manual, Automatic, and Database  
Compliance: IEC 61108-4 beacon standard

## L-Band Sensor Specifications

Sensitivity: -130 dBm  
Channel Spacing: 75 KHz  
Satellite Selection: Manual and Automatic  
Reacquisition Time: 15 seconds (typical)  
Rejection: 15 kHz spacing > 30 dB,  
300 kHz spacing > 60 dB

## Communications

Serial Ports: 2 full-duplex RS232, 1 half-duplex RS422 port  
USB Ports: 1 USB-A  
Baud Rates: 4800 - 115200  
Correction I/O Protocol: RTCM SC-104, L-Dif <sup>7</sup>, RTCM v2 (DGPS), RTCM v3 (RTK), CMR (RTK), CMR+ (RTK) <sup>3</sup>  
Data I/O Protocol: NMEA 0183, Hemisphere GNSS binary <sup>6</sup>  
Timing Output: 1 PPS (CMOS, active high, rising edge sync, 10 kΩ, 10 pF load)

## Power

Input Voltage: 8 to 36 VDC  
Power Consumption: 5.3 W nominal (GPS L1/L2 + GLONASS L1/L2)  
6.2 W nominal (GPS L1/L2 + GLONASS L1/L2 + L-Band)  
0.44 A nominal (GPS L1/L2 + GLONASS L1/L2)  
0.52 A nominal (GPS L1/L2 + GLONASS L1/L2 + L-Band)  
Current Consumption: 500 V  
Power Isolation: Yes  
Reverse Polarity Protection: Yes  
Antenna Voltage: 5 VDC maximum 60mA  
Antenna Short Circuit Protection: Yes  
Antenna Gain Input Range: 10 to 40 dB  
Antenna Input Impedance: 50 Ω

## Environmental

Operating Temperature: -30°C to +70°C (-22°F to +158°F)  
Storage Temperature: -40°C to +85°C (-40°F to +185°F)  
Humidity: 95% non-condensing  
Mechanical Shock: EP455 Section 5.14.1  
Operational (when mounted in an enclosure with screw mounting holes utilized) EP455 Section 5.15.1 Random  
Vibration: CE (IEC 60945 Emissions and Immunity)  
EMC: FCC Part 15, Subpart B  
CISPR22  
Enclosure: IP66 (IEC 60529)

## Mechanical

Dimensions: 20.2 L x 12.0 W x 7.5 H (cm)  
8.0 L x 4.7 W x 3.0 H (in)  
Weight: ~1.1 kg (~2.5 lbs.)  
Status Indications (LED): Power, Primary and Secondary GPS lock, Differential lock, DGPS position, Heading, RTK lock, L-Band DGNSS lock  
Power Switch: Front panel soft switch  
Power/Data Connector: 9-pin ODU metal circular  
Power Connector: 2-pin ODU metal circular  
Data Connector: DB9 (sealed)  
Antenna Connectors: 2 TNC (female)

## Aiding Devices

Gyro: Provides heading smoothing with GNSS. Drift rate is 1° per minute in heading for periods up to 3 minute when loss of GNSS has occurred <sup>4</sup>  
Tilt Sensors: Provide pitch, roll data, assist in fast start-up and heading reacquisition

- 1 Depends on multipath environment, number of satellites in view, satellite geometry, no SA, and ionospheric activity.
- 2 Depends on multipath environment, number of satellites in view, satellite geometry, no SA, and ionospheric activity.
- 3 Requires a subscription from OmniSTAR®
- 4 Depends on multipath environment, number of satellites in view, satellite geometry, baseline length (for differential services), and ionospheric activity.
- 5 Based on a 40 second time constant
- 6 This is the minimum safe distance measured when the product is placed in the vicinity of the steering magnetic compass. The ISO 694 defines "vicinity" relative to the compass as within 5 m (16.4 ft) separation.
- 7 Hemisphere GNSS proprietary

## Authorized Distributor:



Copyright Hemisphere GNSS, Inc. All rights reserved. Specifications subject to change without notice.

Hemisphere GNSS, Hemisphere GNSS logo, Eclipse, Eclipse logo, Vector, VS330, and L-Dif are trademarks of Hemisphere GNSS, Inc. OmniSTAR is a trademark of Trimble Navigation Limited.

Rev. 04/14



Hemisphere GNSS, Inc.  
8444 N 90th Street, Suite 120  
Scottsdale, AZ, USA 85258

Toll-Free: +1-855-203-1770  
Phone: +1-480-348-6380  
Fax: +1-480-270-5070  
precision@hemispheregnss.com  
www.hemispheregnss.com