

Subconn® inline cable information

Circular

Connector	Cable	Nom. OD"	mm	Volts
IL2M & F	16/2	0.365	9.27	600
IL3M & F	16/3	0.385	9.78	600
IL4M & F	16/4	0.410	10.41	600
IL5M & F	18/5	0.465	11.81	600
IL6M & F	16/6	0.520	13.21	600
IL8M & F	16/8	0.555	14.10	600
IL10M & F	18/10	0.577	14.66	600
IL12M & F	18/12	0.605	15.37	600
IL16M & F	18/16	0.704	17.88	600

Low Profile

Connector	Cable	Nom. OD"	mm	Volts
LPIL2M & F	16/2	0.365	9.27	600
LPIL3M & F	16/3	0.385	9.78	600
LPIL4M & F	16/4	0.410	10.41	600
LPIL5M & F	18/5	0.328	8.33	600
LPIL7M & F	16/7	0.520	13.21	600
LPIL9M & F	16/9	0.590	14.99	600

Micro

Connector	Cable	Nom. OD"	mm	Volts
MCIL2M & F	18/2	0.340	8.64	600
MCIL3M & F	18/3	0.360	9.14	600
MCIL4M & F	18/4	0.385	9.78	600
MCIL5M & F	20/5	0.312	7.92	300
MCIL6M & F	20/6	0.315	8.00	300
MCIL8M & F	20/8	0.363	9.22	300
MCIL10M & F	20/10	0.406	10.31	300
MCIL12M & F	20/12	0.436	11.07	300
MCIL16M & F	20/16	0.472	11.99	300
LPMCL7M & F	20/7	0.325	8.26	300

Miscellaneous

Connector	Cable	Nom. OD"	mm	Volts
IL1M & F	1/0-1	0.690	17.50	1000
ILM1M & F	3046	0.142	3.61	600
IL2M & FBC	10/2	0.615	15.62	600
IL3M & FBC	10/3	0.650	16.51	600
HPIL4M & F	8/4	0.715	18.16	600

