
## Nhex-Flex®FP



## Features

TRI-Rated, UL, CSA, IEC Marine UL, TC-ER, 90C 600V Critical Circuit Integrity Fire Resistant

16awg / 1.32 mm2 with insulated ground wire. Halogen Free Low Smoke Cables DNV Marine Type Certified

## Scope

Halogen-free Control, Power and Instrumentation Tray Cable with Tri-rating of UL, CSA, and International Marine approvals. For use in industrial or marine applications with conduit, cable tray applications, and suitable for use in hazardous locations per NEC art. 336, Class 1 Div. 2., CEC. Part 1, Table 19.

## Rating

UL TC-ER, UL1277, NEC art 336 exposed runs
Suitable for class 1 Div 2 Hazardous locations
Sunlight resistant, -25C to 90C Dry
CSA TC CSA C22.2 No. 230, 90C 600V
CSA CIC CSA C22.2 No.239, 90C, 600V
IEC Marine 60092-350,-376, 90C, 250V
LSZH per IEC 60754-1
IEC 60079-14 Annex E Restricted Breathing Test
Construction is per IEC 60079-14 9.3.2 a
Tensile Strength > 8.5 N/mm2 (MPa) (ref IEC 60079-14 2013/Cor 1:2016)
CSA FT-4 Flame, IEC 60332-3-22 Flame
Critical Circuit Integrity Fire Resistant Test IEC 60331-21

	Conductors: Insulation:	16AWG - 7 X .0201 in. stranded nickel plated copper Silicone rubber with fiberglass covering, 200°C			
	Shields:	Pairs are individually shielded with copper tape and have an overall copper tape shield with drain wire.			
Cable Properties	Ground Wire:	Green insulated ground wire outside shields.			
	Jackets:	Halogen-free, olefinic flexible elastomer, flame retardant, oil/vapor/ moisture/sunlight resistant. *Black is the standard color. Blue or red may also be ordered.			
	Wire Coding:	Pairs: Blue & Black with numbered marker tapes Ground: Green			

PART NUMBER	NO. OF COMP.	JACKET THICKNESS	NOM. O.D. JACKET		WEIGHT (LBS.)
PAIRS			INCH	ММ	
FM111716P01	1PR	.043	.372	9.5	81
FM111716P02	2PR	.055	.682	17.3	177
FM111716P04	4PR	.060	.815	20.7	298
FM111716P07	7PR	.080	.944	24.0	298 470

\* P/N ordering – To specify Jacket color, please add following suffixes: -0 for Black Jacket -2 for Red -6 for Blue



Falmat, Inc. 1873 Diamond Street San Marcos, CA 92078 USA 760.471.5400 *Tel* 760.471.4970 *Fax* www.falmat.com

©2016 Falmat Inc. All rights reserved. Made in the USA.